


COMPANY PREPARE			D BY		
EMAIL			PHONE NUMBER		
ADDRESS					
CITY			STATE	ZIP	
PURCHASE ORDER NUMBER			DATE RE	EQUIRED QTY	
TAG					
SPECIAL INSTRUCTIONS (Please note if this is for a quote)					
A	Any interference for Rasco track? ☐ Yes				☐ No
В	☐ B1 - High lift the existing track 24"				
	☐ B2 - Chain link top panel to lean back from the header				
C	Floor to existing horizontal track?			ft _	in
D	What is the existing door thickness?			-	in
E	What is the track width?			□ 2 in	□ 3 in
F	Is the existing track in good condition?			☐ Yes	☐ No
G	When open, can the existing door stop a minimum of 7" above the opening?			☐ Yes	□ No
H	Opening Width:			ft _	in
0	Opening Height:			ft _	in
J	Existing Door Width:			ft	in
К	Existing Door Height:			ft _	in
	Outside to outside of existing track?			ft	in
M	What is the distance from track to bollard? in				
N	If existing door is motor operated, provide an interlock switch on Rasco track. $\ \square$ Yes $\ \square$ No				
0	If Rasco door is to be motor operated, provide an interlock switch.			☐ Yes	□ No
P	If the graduated hinge count is not typical (1,2,3,4 etc.) What is it?				

DOOR SIDE VIEW



NOTES: A torsion bar support is required on all doors 10' or wider.

Switch track cannot be used if existing door has outside pull cables or has TKO, Workhorse or Barcol type tracks.


The Rasco door has outside pull brackets/cables.

DOORTOP ABOVE



Measuring Guide






Track to bollard

To make sure you have clearance for your Rasco door.

Outside to outside of existing track

To ensure a proper fit with your door.





Distance from wall to furthest part of existing track at top of the opening

To ensure a proper seal on the sides, many tracks are farther away from wall at top of opening.

Wall to outside edge of roll or distance to back of roll

To ensure a tight seal on the sides.

